

Technical Data for homogenizer

Model: Tetra Alex 20	Machine No.: 5845514089	Customer: Turkey
-------------------------	----------------------------	---------------------

General:

Capacity: 2000-5000 l/h	Working pressure: 100 bar	Inlet pressure: 3-10 bar	Noise reduction: <input type="checkbox"/>	Sound effect level (acc. to ISO 3746): B(A)
Altitude: <1000 m	Ambient temperature: <40 °C	Total mass: 1274 kg	Centre of gravity (a=): mm	Sound pressure level (distance=1m): dB(A)

Wetend design:

Valve design: Cone <input type="checkbox"/> Mushroom <input checked="" type="checkbox"/> Ball <input type="checkbox"/>	Piston diameter: 50 mm	Piston design: Stainless steel <input checked="" type="checkbox"/> Chromium plated <input type="checkbox"/> Ceramic coated <input type="checkbox"/> Ceramic solid <input type="checkbox"/>	Piston packing: Grooved <input checked="" type="checkbox"/> V-packing <input type="checkbox"/>	Remote ind. of product pressure: <input type="checkbox"/> Feed: <input type="checkbox"/> V DC Signal: <input type="checkbox"/> mA
---	------------------------------	--	--	---

Homogenising device design:

Size of 1st stage: 53/62	Size of 2nd stage 53/62	Remote indication of hydraulic pressure: 1st stage <input type="checkbox"/> 2nd stage <input type="checkbox"/> Feed: <input type="checkbox"/> V DC Signal: <input type="checkbox"/> mA	Remote continuous setting: 1st stage <input type="checkbox"/> 2nd stage <input type="checkbox"/> Feed: <input type="checkbox"/> V DC Control signal: <input type="checkbox"/> mA Amp.
-----------------------------	----------------------------	---	---

Drive Motor:

Manufacture: ABB	Model: M3AA180M 4	Revolution: 1455 rpm	Protection: IP55	Thermistor: <7.5 V DC
Power: 18.5 kW	Voltage: 380 V	Frequency: 50 Hz	Full load current: 35 Amp.	Starting current: 245 Amp.

Hydraulic Unit:

Manufacture: Bosch	Model: 6-4722 5471 81
-----------------------	--------------------------

Hydraulic Motor:

Manufacture: ABB	Model: M2VA71A 4	Revolution: 1410 rpm	Protection: IP55
Power: 0.25 kW	Voltage: 380 V	Frequency: 50 Hz	Rated current: 0.95 Amp.

Pressure Lubrication Motor:

Manufacture:	Model:	Revolution: rpm	Protection:
Power: kW	Voltage: V	Frequency: Hz	Rated current: Amp.

Drive Unit:

V-belt type: SPB	Number of tracks: 2	Motor pulley diameter: 200 mm	Gearbox pulley diameter: 355 mm	V-belt length 2000 mm
---------------------	------------------------	-------------------------------------	---------------------------------------	-----------------------------

Reduction Gear:

Manufacture: Benzler	Model: BT-51	Reduction: 5,760
-------------------------	-----------------	---------------------

Valves:

Cooling water valve: Solenoid <input checked="" type="checkbox"/> Pneumatic <input type="checkbox"/> Voltage: 220 V AC 12 VA	Compressed air supply: bar	Steam valve: Solenoid <input type="checkbox"/> Pneumatic <input type="checkbox"/> Voltage: V AC VA	Compressed air supply: bar	Press. relief valve: 1st Stage <input checked="" type="checkbox"/> 2nd Stage <input checked="" type="checkbox"/> Voltage: 24 V DC 0.75 Amp.	Voltage: 24 V DC 0.75 Amp.
---	-------------------------------	---	-------------------------------	--	-------------------------------

Cooling water supply:

Pressure: 2-4 bar	Consumption: 130 l/h	Temperature: <25 °C	Hardness: <10 °dH
-------------------------	----------------------------	---------------------------	-------------------------

Steam supply:

Pressure: bar	Consumption: kg/h	Temperature: °C
------------------	----------------------	--------------------

Condensate:

Other:

Fluorescent tube: <input type="checkbox"/> Voltage: V AC	Door safety lock: <input type="checkbox"/> Voltage: V AC W	Crankshaft speed sensor: <input type="checkbox"/> Feed: V DC mA
---	--	---

Date: 2004-04-22	Sign: TP	Revision: 1
---------------------	-------------	----------------