

Homogenizer HLI75

- Max. 20.000 Liter per hour
- Homogenizing pressure up to 750 bar
- Absorbed motor power: max. 75 kW
- Optional in aseptic execution
- Poppet valves for low viscous and slight abrasive products
- Ball valve for high viscous and abrasive products
- Integrated lubrication system

*Weight incl. motor: max. 3.800 kg
Technical changes reserved*

Poppet valves

Poppet valves for low viscous and slight abrasive products

| Model | Max. Pressure | Max. Capacity |
|-------|---------------|------------------|
| HLI75 | (bar) | (Liter per hour) |
| -100T | 100 | 20.000 |
| -150T | 150 | 14.000 |
| -200T | 200 | 10.500 |
| -250T | 250 | 8.500 |
| -300T | 300 | 7.000 |
| -350T | 350 | 6.000 |
| -550T | 550 | 3.800 |

Ball valves

For abrasive and high viscous products

| Model | Max. Pressure | Max. Capacity |
|-------|---------------|------------------|
| HLI75 | (bar) | (Liter per hour) |
| -150K | 150 | 14.000 |
| -200K | 200 | 10.500 |
| -250K | 250 | 8.200 |
| -350K | 350 | 5.900 |
| -550K | 550 | 3.700 |
| -750K | 750 | 2.900 |

