



**COOL SOLUTIONS  
FOR PROFESSIONALS**



# ABM023S ABM031S

## BLAST-FREEZER FOR GELATO

### GENERAL FEATURES

- External sides and top in AISI 304 18/10 stainless steel th. 0.6mm (Scotch-Brite satin finish)
- AISI 304 18/10 stainless steel door th. 0.8mm (Scotch-Brite satin finish)
- Internal covering completely radiated in AISI 304 18/10 stainless steel
- Internal base for containment
- High-density expanded polyurethane insulation (about 42 kg/m<sup>3</sup>), without HCFC
- Copper - aluminum evaporator, protected with non-toxic epoxy resins through cataphoresis
- Copper condensing coil with high heat yield aluminium fins
- Anti-condensation resistance positioned on the box under the magnetic gasket
- Ergonomic handle on the complete door length and magnetic gaskets on the 4 sides of the door

### ABM023 AIR

Suitable for **3 x GN 2/3**

### ABM031 AIR

Suitable for **3 x GN 1/1 t**

### INTERNAL SET-UP

- Slides in 18/10 stainless steel, encased on the sides of the room, easily removable for washing
- Core probe (not heated)
- ABM023S: 3 x GN 2/3 stainless steel grids included
- ABM031S: 1 x GN 1/1 stainless steel grid included

### REFRIGERANT UNIT

- Fans with indirect flow onto the product
- Hermetic compressor
- R404A refrigerant liquid
- Evaporator with large exchange surfaces, for high cooling efficiency
- Manual defrosting device and condensation evaporation system without use of electrical energy

### COMMANDS, CONTROLS AND SAFETY DEVICES

- Control and command circuit board equipped with high-visibility custom display, which highlights the status of the appliance at all times
- Circuit breaker for compressor protection

### OPTIONS / ACCESSORIES

- Core probe heated for easy extraction

	ABM023	ABM031
<b>Dimensions</b> (WxDxH) mm	560x560x520	560x700x520
<b>El. power supply</b> (V/ph/Hz)	230 / 1 / 50	
<b>Input electric power</b> (W)	587	587
<b>Max. absorbed current</b> (A)	3,4	3,4
<b>Refrig. Capacity</b> (W)	487	487



**CAPACITY IN  
GELATO TUBS** **2**  
360x165x120mm



**CAPACITY IN  
GELATO TUBS** **1**  
360x250x120mm